



# DECOTRON<sup>®</sup> M50

**Water-based cleaning agent designed for manual cleaning of low-contaminated soldering machines and parts.**

Ready-mix designed for direct use. Designed for cleaning of most types of flux. Developed for areas with common contamination levels, minimum smell.

## Recommended areas for use

---

**Removal of flux residues, dust and grease from reflow ovens, soldering waves and other contaminated surfaces**

## Instructions for use

---

Turn the manual sprayer nozzle from position STOP by 90 ° before first use. Then apply a necessary amount on the surface to be cleaned, wait for several minutes and wipe the surface using a smooth piece of cloth. Repeat the procedure if necessary.



## Information

- High compatibility with material and components of the cleaned devices
- Leave no residue or odor
- Specially developed for cleaning of elements of reflow ovens
- No flash point
- Suitable for cleaning of flux residues of all types of soldering flux
- Environmentally-friendly – biodegradable
- A special sprayer creates “active foam” which remains active on vertical surfaces for a longer time

## Table of physical and chemical properties

Product appearance:	clear liquid
Colour:	transparent
Odour:	ether-like
pH value:	10 - 11
VOC content:	8 %
Flash point:	non-flammable
Density at 25 °C:	0,99 kg/l



## Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at [www.dct.cleaning](http://www.dct.cleaning)

Date of revision:  
**07. 06. 2021**

Check SDS prior to use.  
Check material compatibility in case of contact with sensitive materials susceptible to chemical stress.

Decotron<sup>®</sup> is a registration trademark  
of DCT Czech s.r.o.



# DECOTRON® M50

## General information



### Packing

1 litre bottle; 5, 10, 25 litre can



### Transport

UN number: 1824

Transport hazard class: 8



### Handling

Wear nitrile gloves while manipulating with cleaning agent.

It is necessary to stir well the can before use.



### Storage

Should be stored in closed containers, in ventilated areas

At temperature 5 – 25 °C



### Shelf life:

The minimum shelf life for this product is 5 years.

## Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at [www.dct.cleaning](http://www.dct.cleaning)

## Product features

RoHS and REACH compliant, biodegradable, does not contain any halogenated compounds.



We are certified as part of a worldwide quality management system by LLOYD'S.

Date of issue:  
**07. 06. 2021**

Check SDS prior to use.  
Check material compatibility in case of contact with sensitive materials susceptible to chemical stress.

Decotron® is a registration trademark of DCT Czech s.r.o.