

Antifoam 03

Water dispersible chemical defoaming agent.

Recommended areas for use

To knock down the foam in cleaning or rinsing fluid in spray in air or air bubble cleaning systems.



Instructions for use

Dilution ratio: 1:100

Recommended process temperature: 25 – 45°C

Shake befor use



Product information

- Possess lower surface tension than the systém to which is added
- Disperse readily in the system
- Leave no residue or odor
- Doesn't contain silicone

Physical and chemical properties

Product appearance: milky liquid
Odour, aroma: organic
VOC content: 60%
pH: 7
Flash point: no
Density at 20°C: 0,98 kg/l



Date of issue/revision:

Consult MSDS prior to use.

27 March 2017

www.dct.cleaning page 1 / 2



Antifoam 03

General information



Packing

1 litres, 5 litres

Transport



UN number: No.

Transport hazard class: No.



Handling

Wear nitrile gloves while manipulation with the cleaning fluid.



Storage

Should be stored in closed containers, in ventilated areas at the temperature from 5 to 25 $^{\circ}$ C.



Shelf life

The minimum shelf life for this product is 2 years.

Return the used product for proper disposal to the nearest authorized collection location.

Technical support

For process implementation and setting, optimization and solving of process issues, trial test, your DCT specialist at www.dct.cleaning

contact

Product features

RoHS and REACH compliant, biodegradable, does not contain any halogenated compounds







We are certified as part of a worldwide quality management system by LLOYD'S



Date of issue/revision:

Consult MSDS prior to use.

27 March 2017

www.dct.cleaning page 2/2