

PROTON® 23

Alcohol-based cleaning fluid determined to remove residues of a solder paste and SMT adhesives from printing stencils, PCBs misprints and squeegees.

Ready-mix, intended for direct use.

Specially designed for wet cleaning process in screen printing.

Effective for all types of solder pastes and most types of SMT adhesives.



Recommended areas for use

Recommended cleaning technology

1. Solder paste (unsoldered)	Wet cleaning process in screen printers		
2. SMT adhesive (uncured)	Manual removing using cleaning fluid and a		
	wipe		

Process table

Screen printing	Proton® 23	х	х	Vacuum Paper roll
Cleaning technology	Cleaning	1. rinse	2. rinse	Drying



Product information

- High cleaning efficiency / fast evaporation
- High compatibility with material and components of the screen printers
- Tenzide-free, no solid residues on the cleaned surface

Table of physical and chemical properties

Product appearance: one phase clear liquid
Colour: colourless / yellowish
Odour: ether-like

Odour: ether-lik
VOC content: 100 %

Recommended process temperature: room temperature

Flash point: 40 °C Density at 20 °C: 0,9 kg/l





Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at www.dct.cleaning

Date of issue: **02. 03. 2020**

Check SDS prior to use.

Check material compatibility in case of contact with sensitive materials

susceptible to chemical stress.

Proton[®] is a registration trademark of DCT Czech s.r.o.

www.dct.cleaning page 1 / 2

TECHNICAL DATA SHEET



PROTON® 23

General information



Packing

25 litres; 5 litres, 1 litre can



Transport

UN number: 3092

Transport hazard class: 3



Handling

Wear nitrile gloves while manipulating with cleaning agent. It is necessary to stir well the can before use.



Storage

Should be stored in closed containers, in ventilated areas At temperature 5 – 25 $^{\circ}\text{C}$



Shelf life:

The minimum shelf life for this product is 5 years.

Product features

RoHS and REACH compliant, biodegradable, does not contain any halogenated compounds.









We are certified as part of a worldwide quality management system by LLOYD'S.

Date of issue:

Check SDS prior to use.

02. 03. 2020

Check material compatibility in case of contact with sensitive materials susceptible to chemical stress.

Proton[®] is a registration trademark

ve materials of DCT Czech s.r.o.

www.dct.cleaning page 2 / 2