

## PROTON® 29

Alcohol-based cleaning fluid determined to remove residues of a solder paste and SMT adhesives from printing stencils, PCBs misprints and squeegees.

Ready-mix, intended for direct use.

Specially designed for wet cleaning process in screen printing.

Effective for all types of solder pastes and most types of SMT adhesives.



## **Recommended areas for use**

### Recommended cleaning technology

1. Solder paste (unsoldered)	Wet cleaning process in screen printers
2. SMT adhesive (uncured)	Manual removing using cleaning fluid and a wipe

### **Process table**

Screen printing	Proton <sup>®</sup> 29	Х	Х	Vacuum Paper roll
Cleaning technology	Cleaning	1. rinse	2. rinse	Drying



evaporation

### **Product information**

- High cleaning efficiency / fast evaporation
- High compatibility with material and components of the screen printers
- EKRA approved cleaning fluid
- Tenzide-free, no solid residues on the cleaned surface

### **Table of physical and chemical properties**

Product appearance: one phase clear liquid colour: colourless / yellowish

Odour: ether-like VOC content: 100 %

Recommended process temperature: room temperature

Flash point:  $40 \,^{\circ}\text{C}$  Density at  $20 \,^{\circ}\text{C}$ :  $0.9 \, \text{kg/l}$ 



### **Technical support**

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at <a href="https://www.dct.cleaning">www.dct.cleaning</a>

Date of issue: **02. 03. 2020** 

Check SDS prior to use.

Check material compatibility in case of contact with sensitive materials susceptible to chemical stress.

Proton® is a registration trademark of DCT Czech s.r.o.

www.dct.cleaning page 1 / 2

## TECHNICAL DATA SHEET



# PROTON® 29

### **General information**



### **Packing**

25 litres; 5 litres, 1 litre can



### **Transport**

UN number: 3092

Transport hazard class: 3



### **Handling**

Wear nitrile gloves while manipulating with cleaning agent.

It is necessary to stir well the can before use.



### **Storage**

Should be stored in closed containers, in ventilated areas

At temperature 5 – 25 °C



### **Shelf life:**

The minimum shelf life for this product is 5 years.

### **Product features**

RoHS and REACH compliant, biodegradable, does not contain any halogenated compounds.









We are certified as part of a worldwide quality management system by LLOYD'S.

Date of issue:

Check SDS prior to use.

**02. 03. 2020** Check material compatib

Check material compatibility in case of contact with sensitive materials susceptible to chemical stress.

Proton® is a registration trademark of DCT Czech s.r.o.

www.dct.cleaning page 2 / 2