



# STENCIL CLEANER 11

**Alcohol-based cleaning fluid designed for manual pre-cleaning and cleaning of printing stencils and squeegees.**

Ready-mix, intended for direct use.

Designed for cleaning most soldering paste and SMT adhesive types.

Recommended for stencil pre-cleaning before machine cleaning or as a manual solution for stencil cleaning.



## Recommended areas for use

**Removing soldering paste and SMT adhesive residues and other contaminations (dust, grease).**

## Instructions for use

Turn the manual sprayer nozzle from position STOP to 90° before the first use. Then apply a necessary amount to the part to be cleaned, wait for several minutes and wipe residues using a wiper. Repeat the procedure if necessary.

## Product information

- Universal solution for all types of solder pastes and most SMT adhesive types.
- High material compatibility
- Compatible with both lead and non-lead processes
- Environment-friendly, biodegradable
- Tenzide-free, no solid residues on the cleaned surfaces.



## Table of physical and chemical properties

|                     |                        |
|---------------------|------------------------|
| Product appearance: | one phase clear liquid |
| Odour:              | ether-like             |
| pH value:           | N/A                    |
| VOC content:        | 100 %                  |
| Flash point:        | 49 °C                  |
| Density at 25 °C:   | 0,9 kg/l               |



## Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at [www.dct.cleaning](http://www.dct.cleaning)

Date of issue:

28. 04. 2021

Check SDS prior to use.

Check material compatibility in case of contact with sensitive materials susceptible to chemical stress.



# STENCIL CLEANER 11

## General information



### Packing

1 litre bottle; 5, 10 and 25 litre can



### Transport

UN number: 3271

Transport hazard class: 3



### Handling

Wear nitrile gloves while manipulating with cleaning agent.

It is necessary to stir well the can before use.



### Storage

Should be stored in closed containers, in ventilated areas

At temperature 5 – 25 °C



### Shelf life:

The minimum shelf life for this product is 2 years.

Return the used product for proper disposal to the nearest authorized collection location.

## Notification

The fluid may become yellow-to-brown as a result of a temperature change or under the influence of light and air. This is a common phenomenon and not a flaw and in no way changes the properties of the product.

## Product features

RoHS and REACH compliant, biodegradable, does not contain any halogenated compounds.



RoHS  
Compliant



REACH  
SVHC



BIODEGRADABLE



We are certified as part of a worldwide quality management system by **LLOYD'S**.

Date of issue:

28. 04. 2021

Check SDS prior to use.

Check material compatibility in case of contact with sensitive materials susceptible to chemical stress.